

Technical Datasheet

Bioten Ultra VI

Special cleaner for the removal of sealants

BIOTEN Ultra VI is a special intensive cleaner for the quick and effective removal of sealants, adhesive residue, grease, resins etc...

- Fast working time
- Good cleaning action
- Odourless, therefore minimal impact on room air
- Excellent solvent power
- Does not require hazard classification
- VOC free

BIOTEN Ultra VI has a broad-based range of uses, such as in the

aviation industry, metal processing industry, trade and commerce

Uses

Use BIOTEN Ultra VI concentrated. The material is sprayed or can be used in an immersion process. Wipe the surface with an absorbent cloth after use.

BIOTEN Ultra VI contains no chlorinated hydrocarbons nor CFCs and can be offered as an effective alternative to these products.

Important note

Checktolerability on painted surfaces, plastic and rubber components!

Specification Data

Parameter	Unit	Value	Method
Ester content	Gew.%	min. 99,0	GC
Water content	Gew.%	max. 0,1	ASTM D-1364
Acid number	mg KOH/g	max. 0,3	ASTM D-1613
Dimethyladipate	Gew.%	1025	GC
Dimethylglutarate	Gew.%	5565	GC
Dimethylsuccinate	Gew.%	1525	GC
Methanol	Gew.%	max. 0,2	GC
Colour number	APHA	max.15	ASTM D5386
Density	g/ml	1,0751,093	DIN EN ISO 12185
Refractive index (nD20)		1,4221,426	DIN 51423
Appearance		visually	clear, colourless