

Technical Datasheet

LCT Edeltahllotion

LCT Edeltahllotion is a highly efficient product specially developed for the cleaning and caring of stainless steel, aluminium, non-ferrous metals as well as glass and plastics. It removes dust, fingerprints, oil and light lime soiling. It Gives a dry brilliant protective film and protects against finger prints and new dirt

- For a thousand and one uses, silicone free
- Simple to use – no streaks

Chemical characterisation:

Water-oil emulsion

Technical data:

Appearance : liquid

Colour : white

Odour : characteristic

Boiling temperature : ca. 100 °C

Solidifying temperature : < 0 °C

Flash point : not relevant

Ignition temperature : not relevant

Lower explosion limit : not relevant

Upper explosion limit : not relevant

Density (20 °C) : ca. 0.94 g/cm³

pH-value : ca. 11.4

VOC (EG) : 0 Wt %

VOC (CH) : 0 Wt %

Storage:

Keep container tightly closed. Keep/store only in original container. Protect against sub-zero temperatures. Optimized storage temperature is between 2 °C up to 35 °C. The product is storable in closed original packaging for at least 12 months. Starting date is the date of production.

Storage class (acc. TRGS 510): 12

Disposal advices:

The waste codes are recommendations based on the schedule use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances.

Waste code acc. EWC/AVV for unused product

20 01 29 detergents containing dangerous substances

Waste code acc. EWC/AVV for packaging

15 01 02 plastic packaging

Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

Laue Cleaning Technology GmbH